

Model: CL-HDMI-1701

1U Rackmount 17" LCD with 1 port HDMI KVM console, 1 x 1.8 meter KVM Cable



Main Feature

- One console controls one connected computer / server
- A-Grade 17" LED-backlit LCD panel with maximum resolution of 1280 x 1024
- LCD module rotates up to 120 degrees for a more comfortable viewing angle
- Supporting DOS, Windows, Netware, Unix, Linux, Mac OS
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- 1U 19" rack mountable design, metal case - Integrated full size keyboard and touchpad
- Easy for operate, allow smoothly pulling with self-locking at end position
- Customized Keyboard Language support upon request

Specification		
Product Model		CL-HDMI-1701
LCD	Size	A-Grade 17" LED-backlit LCD panel (Ratio: 4:3)
	Resolution	1280 x 1024 @ 60Hz
	Max. color	16.7M
	Luminance	250 cd/m ²
	View Angle	140°(H), 130°(V)
	Pixel Pitch	0.264 x 0.297 mm
	Contrast Ratio	1000 : 1
	LCD MTBF	50,000 hours
Computer Connections	Direct	1
Computer Port Selection		OSD, Hot Key, Push Button

Connector	Power	12 VDC Input
	Computer	1 x HDMI Female port
	Front USB port	1 x USB-B Type
LEDs	Port	1
	Power	1
Button / Switch	Power Switch	Button
	LCD Adjustment	Button
Hotkey		Provide various Hotkey (Scroll/Shift/ Alt/ Ctrl + Num)
Auto-Scan Intervals		3 - 60 Seconds
Power Rating (AC to 12VDC/4A adapter)		100-240VAC, 50/60Hz
Environment	Operating Temperature	-10 - 50°C
	Store Temperature	-20 - 60°C
	Humidity	0-80% RH, NC
Housing		Heavy Duty Steel
Size		1U, 19" Rack mount
Rack Installation Depth (front rails to rear rails)		410 - 750mm (Minimum to Maximum adjustable)
Net / Gross Weight		17 / 19KG
Dimensions (W*D*H)		443 x 410 x 45 mm
Certificated		CE/FCC
Ordering Information		
CL-HDMI-1701	1U Rackmount 17" LCD with 1 port HDMI KVM console, 1 x 1.8 meter KVM Cable	

Structure Diagram (mm)

