

Model: IDPM-17
17" Industrial Panel Monitor



Main Feature

- 17" SXGA TFT LCD Panel support 1280x1024 pixels
- Steel front bezel with strengthen glass
- Rugged construction design
- Input signal : VGA + USB / RS232 (for Touch Screen)
- OSD control keys to optimize the display (Hot-Key for quick "Brightness & Contrast" adjustment)
- NEMA4 / IP 65 compliant front panel
- AC 100-240V wide range external AC adapter
- Panel mounting with clip
- Meet standard VESA hole (75x75 & 100X100mm), support desktop stand/wall mount /swing arm mounting

| Specification | |
|----------------------------------|---|
| Product Model | IDPM-17 |
| LCD Panel | Display Type : 17" SXGA TFT LCD Resolution : 1280x1024 Max. color : 16M Luminance : 300 cd/m ² View Angel : 140° (H) , 130° (V) Pixel Pitch : 0.297 x 0.297 mm Contrast Ratio : 500 : 1 Response Time : 8 ms LED backlight lifecycle : 50,000hrs |
| Signal Input | VGA (15 pin D-sub connector) |
| Protect Glass | 3 mm strengthen glass |
| OSD | Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall |
| Signal Connectivity (optional) | BNC input |
| Power Supply | Input: 100-240VAC,50/60Hz |

| | |
|----------------------------|--|
| | Output: DC12V@ 4A /48W, external AC power adapter |
| Construction | Heavy duty steel and aluminum front panel |
| Environment | Operating temperature: 0 °C to 60 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 17 to 500HZ 1G PTP Shock: 1G /peak(11m sec) |
| Safety | CE/FCC/Rohs |
| Dimension W x H x D (mm) | Dimensions: 432 x 353 x 52 mm |
| Weight | NET weight: 6.3 KG; Gross weight: 8.7 KG |

Ordering Information

| | |
|---------------|------------------------------|
| IDPM-17 | 17" Industrial Panel Monitor |
| Optional: BNC | Support BNC Input |

Structure Diagram (Mounting Hole Size: 414 x 335 mm) Unit: mm

