

Model: IDPM-19
19" Industrial Panel Monitor



Main Feature

- 19" SXGA TFT LCD Panel support 1280x1024 pixels
- Aluminum front bezel with strengthen glass
- Rugged construction design
- Input signal : VGA + USB / RS232 (for Touch Screen)
- OSD control keys to optimize the display (Hot-Key for quick "Brightness & Contrast" adjustment)
- NEMA4 / IP 65 compliant front panel
- AC 100-240V wide range external AC adapter
- Panel mounting with clip
- Meet standard VESA hole (75x75 & 100X100mm), support desktop stand/wall mount /swing arm mounting

Specification	
Product Model	IDPM-19
LCD Panel	Display Type : 19" SXGA TFT LCD Resolution : 1280x1024 Max. color : 16M Luminance : 300 cd/m ² View Angel : 160° (H) , 160° (V) Pixel Pitch : 0.297 x 0.297 mm Contrast Ratio : 700 : 1 Response Time : 8 ms LED backlight lifecycle : 50,000hrs
Signal Input	VGA (15 pin D-sub connector)
Protect Glass	3 mm strengthen glass
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall
Signal Connectivity (optional)	BNC input
Power Supply	Input: 100-240VAC,50/60Hz

	Output: DC12V@ 4A /48W, external AC power adapter
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: 0 °C to 60 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 17 to 500HZ 1G PTP Shock: 1G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 461 x 386 x 57 mm
Weight	NET weight: 7.8 KG; Gross weight: 9.8 KG

Ordering Information

IDPM-19	19" Industrial Panel Monitor
Optional: BNC	Support BNC Input

Structure Diagram (Mounting Hole Size: 443 x 368 mm) Unit: mm

