


Model: IPC-2408
2U Server Case, 8 Hot-Swappable SAS/SATA Drive Bay, MINI-SAS
backplane (SFF-8087, Max. 12Gb/s)



Specification

- Form Factor: 2U, 19'' Rackmount Chassis
- Color: Silver and Black
- Motherboard Support: MINI-ITX (6.7''x6.7''), Mirco ATX (9.6''x9.6''), ATX (12"x9.6"), CEB (12"x10.5"), EEB (12"x13")
- Processor Support: Supports dual, single Intel® / AMD processors
- Power Supply Support: standard 2U ATX, 1+1 Redundant
- Dimensions (H x W x D): 89mm x 480mm x 690mm
- Expansion Slots: 7
- Drive Bay: 8 x 2.5'' / 3.5'' hot-swappable SAS/SATA trays, 1 x slim DVD bay, 2 x 2.5'' / 3.5" bay
- Backplane: 2 x SFF-8087 Mini SAS connectors (Max. 12Gb/s)
- Front Panel: Power ON/OFF switch, System Reset switch, 2 x USB 3.0 port
- Front LED: 1 x Power ON, 1 x HDD activity, 3 x LAN activity, 1 x Alarm
- System Cooling: 4 x 80mm middle fans (Hot-swap type, Molex connector)
- Operating Temperature: 0/50 °C
- Storage Temperature: -20/60 °C
- Storage Humidity: 10% to 90%, non-condensing
- Packing: Double Carton boxes, 160mm x 560mm x 830mm (H x W x D)
- Weight: 10.5 Kg(net), 12.5 Kg (gross)

Optional items

- Sliding Rail (For server rack depth 800 to 1000mm)
- Telescopic Sliding Rails For server rack depth 800 to 1200mm
- 2U 500watt Power Supply Unit
- 2U 800 watt Redundant Power Supply Unit