

Product Model: KDP-104

4 port USB DisplayPort / Audio KVM switch with DP KVM Cable



Main Features

- 4-Port USB DisplayPort/Audio KVM Switch (4K Supported and Cables included)
- One USB console controls four DP interface computers and one additional USB devices
- One front port USB hub 2.0 built in, fully compliant USB 2.0 specification
- Superior video quality - supports 480i, 480p, 720p, 1080i, 1080p, and 4K (resolution: 3,840x2,160 @ 60Hz)
- Independent switching of KVM, USB peripheral, and audio focus via front panel push buttons and hotkeys
- DisplayPort 1.2 compliant; HDCP compliant
- Multiplatform support - Windows, Linux, and Mac
- BIOS hardware connection, no need driver program and controlling software
- Auto scan Mode for monitoring all connected computers

Specification	
Product Model	KDP-104
Computer Connections	4
Port Selection	Front push button and Hot key
Front LED Indicator	4 x On-line (Red), 4 x Selected (Green)
Connectors	
Console Ports	2 x USB Type A Female (rear panel) 1 x DisplayPort Female (Black) 2 x 3.5 mm Audio Jack Female
KVM Port	4 x USB Type B Female 4 x DisplayPort (Black) 4 x 3.5 mm Audio Jack Female
USB Hub	1 x Front USB Type A Female



Power	1 x DC Jack	
Video Resolution	480i, 480p, 720p, 1080i, 1080p, and 4K (3,840x2,160 @ 60Hz)	
Scan Interval	1-99 seconds (default: 5 sec.)	
Power Consumption	5 VDC / 4 Watt	
Environmental	Operating Temperature	0°C to 50°C
	Storage Temperature	-20°C to 60°C
	Humidity	10% to 90%, non-condensing
Net Weight	0.9 Kg	
Dimensions (W x D x H)	202 x 110 x 44 mm	

Ordering Information	
KDP-104	4 Port USB DisplayPort / Audio KVM Switch, with 4 x 1.8 meter KVM Cables - USB & DP interface