

## Model: KH-202

2 Port USB Dual Display HDMI / Audio KVM Switch, with 2 x 1.8 meter KVM Cables - USB & HDMI interface



Primary Display - HDMI Line ————  
Secondary Display - HDMI Line ————

## Main Feature

- 2 Port HDMI USB2.0 KVM Switch
- One dual-screen USB console controls two HDMI interface computers and one additional USB devices
- One front port USB hub 2.0 built in, fully compliant USB 2.0 specification
- Superior video quality - supports 480i, 480p, 720p, 1080i, 1080p, and 4K (resolution: 3,840x2,160 @ 30Hz)
- Independent switching of KVM, USB peripheral, and audio focus via front panel push buttons and hotkeys
- HDMI digital monitor support - fully compliant with HDMI; also HDCP compliant
- Dolby True HD and DTS HD Master Audio support
- Multiplatform support - Windows, Linux, and Mac
- BIOS hardware connection, no need driver program and controlling software
- Auto scan Mode for monitoring all computers and HDMI devices

Specification		
Product Model	KH-202	
Computer Connections	2	
Port Selection	Front push button or Hot-key	
Front LED Indicator	2 x On-line (Red), 2 x Selected (Green)	
<b>Connectors</b>		
Console Ports	2 x USB Type A Female (rear panel) 1 x HDMI Female (Black)	
KVM Port	2 x USB Type B Female 2 x HDMI Female (Black) 2 x 3.5 mm Audio Jack Female	
USB Hub	1 x Front USB Type A Female	
Power	1 x DC Jack	
Video Resolution	480i, 480p, 720p, 1080i, 1080p, and 4K (3,840x2,160 @ 30Hz)	
Scan Interval	1-99 seconds (default: 5 sec.)	
Power Consumption	5 VDC / 5 Watt	
Environment	Operating Temperature	0 to 50°C
	Store Temperature	-20 to 60°C
	Humidity	10% to 90%, non-condensing
Net / Gross Weight ( KG )	0.6 Kg	
Dimensions ( W x H x D )	132 x 92 x 66 mm	
<b>Ordering Information</b>		
KH-202	2 Port USB Dual Display HDMI / Audio KVM Switch, with 2 x 1.8 meter KVM Cables - USB & HDMI interface	