

Model: KVM-15xxCOMBO-S (KVM-1501COMBO-S, KVM-1508COMBO-S, KVM-1516COMBO-S)
1U Rackmount 15" TFT LCD KVM (Short Depth - 406mm)



Main Feature

- 1 PS/2 console controls 1/8/16 directly connected computers
- 86 keys keyboard with touch pad
- Cascade switches up to 8 levels and Mix switches between Cat5 & DB-15 KVM
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports

| Specification | | | | |
|------------------------------|------------|--|-----------------|-----------------|
| Product Model | | KVM-1501COMBO-S | KVM-1508COMBO-S | KVM-1516COMBO-S |
| LCD | Size | 15" TFT | | |
| | Resolution | 1024 x 768 | | |
| | Max.color | 16.7 M | | |
| | Luminance | 300 cd/m2 | | |
| | View Angle | 178° (H) , 178° (V) | | |
| LEDs / Port | | 1 | 8 | 16 |
| Power | | 1 | | |
| Computer Connections | | 1 | 8 | 16 |
| Maximum Computer Connections | | 225 | 232 | 240 |
| Computer Connectors | | 2 x PS2, 1 x USB, 1 x VGA / 8 x DB -15 female / 16 x DB -15 female | | |
| Daisy Chaining | | Daisy Chainable up to 8 levels ; Connector : DB-15 (female type) | | |
| Computer Selection | | On Screen Display (OSD) , Hot Key , Push Button | | |

| | | |
|-----------------------------------|--|---------------------------|
| Hotkey | Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win) | |
| Auto-Scan Intervals | 5 - 99 Sec. | |
| Keyboard / mouse Emulation | PS/2 | |
| Power Adapter | AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt | |
| Housing | Metal | |
| Size | 19" Rack mount, 1U | |
| Environment | Operating Temperature | 0 - 50°C |
| | Store Temperature | -20 -60°C |
| | Humidity | 10% to 90%,non-condensing |
| Physical Dimensions (W x H x D) | 482.6 x 43.6 x 406.4 mm | |
| Certificated | CE/FCC | |
| Ordering Information | | |
| KVM-1501COMBO-S | 1U Rackmount 15" TFT LCD ,with 1 port KVM switch (Short Depth) | |
| KVM-1508COMBO-S | 1U Rackmount 15" TFT LCD, with 8 port KVM switch (Short Depth) | |
| KVM-1516COMBO-S | 1U Rackmount 15" TFT LCD, with 16 port KVM switch (Short Depth) | |
| KCVU-018 (optional) | USB, 2 in 1 KVM Cable , 1.8 meter length | |
| KCVU-030 (optional) | USB, 2 in 1 KVM Cable , 3.0 meter length | |
| KCVU-050 (optional) | USB, 2 in 1 KVM Cable , 5.0 meter length | |
| KCVP-018 (optional) | PS/2, 3 in 1 KVM Cable , 1.8 meter length | |
| KCVP-030 (optional) | PS/2, 3 in 1 KVM Cable , 3.0 meter length | |
| KCVP-050 (optional) | PS/2, 3 in 1 KVM Cable , 5.0 meter length | |

Structure Diagram

Unit :mm

