

Model: KVM-1701W-COMBO-S (1U Rackmount 17.3" Full HD LCD with 1 port KVM switch - Short Depth)
KVM-1708W-COMBO-S (1U Rackmount 17.3" Full HD LCD with 8 port KVM switch - Short Depth)
KVM-1716W-COMBO-S (1U Rackmount 17.3" Full HD LCD with 16 port KVM switch - Short Depth)



Main Feature

- 1 PS/2 console controls 1/8/16 directly connected computers
- 88 keys keyboard with touch pad
- Cascade switches up to 8 levels and Mix switches between Cat5 & DB-15 KVM
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports

Specification				
Product Model		KVM-1701W-COMBO-S	KVM-1708W-COMBO-S	KVM-1716W-COMBO-S
LCD	Size	17.3" Full LED Panel		
	Resolution	1920 X 1080		
	Max. color	26.2M		
	Luminance	300 cd/m2		
	View Angel	140°(H) , 120°(V)		
	Pixel Pitch	0.1989 x 0.1989 mm		
	Contrast Ratio	500 : 1		
LEDs / Port		1	8	16
Power		1		
Computer Connections		1	8	16
Maximum Computer Connections		225	232	240
Computer Connectors		2 x PS2, 1 x USB, 1 x VGA / 8 x DB -15 female / 16 x DB -15 female		
Daisy Chaining		Daisy Chainable up to 8 levels ; Connector : DB-15 (female type)		
Computer Selection		On Screen Display (OSD) , Hot Key , Push Button		
Hotkey		Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)		
Auto-Scan Intervals		5 ~ 99 Sec.		
Keyboard / mouse Emulation		PS/2		
Power Adapter		AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt		
Housing		Metal		
Size		19" Rack mount, 1U		
Environment	Operating Temperature	0-50°C		
	Store Temperature	-20-60°C		
	Humidity	10% to 90%,non-condensing		
Net / Gross Weight		14kg / 17kg		
Physical Dimensions (W x H x D)		483 x 42 x 457 mm		
Packing Dimensions (W x H x D)		605 x 168 x 700 mm		
Certificated		CE/FCC		
Ordering Information				
KVM-1701W-COMBO-S		1U Rackmount 17.3" Full HD LCD, with 1 port KVM switch (Short Depth)		
KVM-1708W-COMBO-S		1U Rackmount 17.3" Full HD LCD, with 8 port KVM switch (Short Depth)		
KVM-1716W-COMBO-S		1U Rackmount 17.3" Full HD LCD, with 16 port KVM switch (Short Depth)		
KCVU-018		USB, 2 in 1 KVM Cable , 1.8 meter length		
KCVU-030		USB, 2 in 1 KVM Cable , 3.0 meter length		
KCVU-050		USB, 2 in 1 KVM Cable , 5.0 meter length		
KCVP-018		PS/2, 3 in 1 KVM Cable , 1.8 meter length		
KCVP-030		PS/2, 3 in 1 KVM Cable , 3.0 meter length		
KCVP-050		PS/2. 3 in 1 KVM Cable , 5.0 meter length		

Structure Diagram Unit : mm

