

Model: OFM-21W-HD
21.5" Industrial Open Frame Panel Monitor



Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 21.5" Full HD LED Panel support 1920 x 1080 pixels
- Input signal : VGA + DVI
- OSD control keys to optimize the display
- 12 VDC input, with AC 100-240V wide range external AC adapter
- Panel mounting design
- Rugged construction design with Heavy Duty Steel Chassis
- Support standard VESA mounting (75 & 100 mm)

Specification	
Product Model	OFM-21W-HD
LCD Panel	Display Type : 21.5" Full HD (AUO LED Panel) Resolution : 1920 x 1080 Max. color : 16.7M Brightness : 300 cd/m2 View Angel : 178° (H) , 178° (V) Contrast Ratio : 1000 : 1 MTBF : 50,000hrs
Signal Input	VGA (15 pin D-sub connector) + DVI (DVI-D)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and Source
Signal Connectivity (optional)	Support AV input (VGA + BNC)
Power Supply	Input: 100-240VAC,50/60Hz Output: DC12V@ 4A /48W ,external ac adapter
Construction	Heavy duty steel chassis
Environment	Operating temperature: 0° C to 50° C Storage temperature: -10° C to 60° C

	Storage humidity: 10% to 95%, non-condensing Vibration: 5 to 500HZ 1G PTP Shock: 15G peak (11m second)
Compliance	CE/FCC/ROHS
Dimension W x H x D (mm)	562 x 353 x 39

Ordering Information

OFM-21W-HD	21.5" Industrial Open Frame Panel Monitor
Optional: AV	Support AV Input (VGA + BNC)

Structure Diagram Unit: mm

