


**Model: OFM-21WT-HD**  
**21.5" Industrial Open Frame Panel Monitor, with IR Touch Screen**



## Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 21.5" Full HD LED Panel support 1920 x 1080 pixels
- Input signal : VGA + DVI
- OSD control keys to optimize the display
- 12 VDC input, with AC 100-240V wide range external AC adapter
- Panel mounting design
- Rugged construction design with Heavy Duty Steel Chassis
- Support standard VESA mounting (75 & 100 mm)

Specification	
Product Model	OFM-21WT-HD
LCD Panel	Display Type : 21.5" Full HD (AUO LED Panel) Resolution : 1920 x 1080 Max. color : 16.7M Brightness : 300 cd/m2 View Angel : 178° (H) , 178° (V) Contrast Ratio : 1000 : 1 MTBF : 50,000hrs
Signal Input	VGA ( 15 pin D-sub connector ) + DVI (DVI-D)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and Source
Touch Screen 	Internal USB or RS-232 interface controller - <u>IR Touch</u> Type: Infrared position sensor Resolution: 4096 x 4096 Light transmission: 95% - 100% Power consumption: <5V @2mA Positional Accuracy: 2mm Responding time: <16ms

	Touch Activation Force: No pressure required Operation system : Window 2000 / XP / Vista / 7 / CE, DOS , Linux
Signal Connectivity ( optional )	Support AV input (VGA + BNC)
Power Supply	Input: 100-240VAC,50/60Hz Output: DC12V@ 4A /48W ,external ac adapter
Construction	Heavy duty steel chassis
Environment	Operating temperature: 0 °C to 50 °C Storage temperature: -10 °C to 60 °C Storage humidity: 10% to 95%, non-condensing Vibration: 5 to 500HZ 1G PTP Shock: 15G peak (11m second)
Compliance	CE/FCC/ROHS
Dimension W x H x D ( mm )	562 x 353 x 39

## Ordering Information

OFM-21WT-HD	21.5" Industrial Open Frame Panel Monitor, with IR Touch Screen
Optional: AV	Support AV Input (VGA + BNC)

## Structure Diagram Unit: mm

