

**Model: PCI-108
Serial Card**



Features

- Serial communication speed up to 115.2 kbps.
- 16 byte FIFO and on-chip H/W, S/W flow control
- Plug & Play, I/O address and IRQ assigned by BIOS
- Compatible of PCI 33/66 MHz Ver. 3.0, 2.3, 2.2 & 2.1
- Drivers provided for Windows98/NT4.0/ 2000/ XP/ Vista and Linux
- CE/FCC /ROHS of certification
- Application: Bank, POS of system, ATM, Automation, Monitoring, Stock, Transmission

Product Specifications

- Number of port: 8
- Serial standards: RS232
- Serial signals: TXD, RXD, CTS, RTS, GND DTR, DSR, DCD
- RI Data Bits: 5 6 7 8
- Stop Bits: 1 1.5 2
- IRQ/ IO: Assigned by BIOS (compatible of 16C1050)
- Parity: None, even, odd, space, mark
- Connector: DB62 to 8 x DB9 connector (9 pin Male)
- FIFO 16_byte FIFO (CTS/RTS XON/XOFF)
- ESD Protection: 15KV
- Baud rate: 75bps–115.2Kbps

System Requirement

- PCI-X/PCI Rev.2.3 compatible (32-bit 33/66MHZ)
- DOS/LINUX2.4/LINUX2.6/WIN98/WIN2000/WINXP/32/64/WIN2003/WIN7/WIN2008 etc