

Model: RPC-710T
4U 19'' Rackmount Chassis, with 8'' LCD & Touch Screen



Main Feature

- 4U 19'' Rack Mount Design
- Front 8'' TFT LCD display
- Shock-resistant Driver Bay to hold 3x 5.25'' CD-ROM and 1x 3.5'' FDD(External), and 1x 3.5'' HDD(Internal)
- Flexible mechanical design supports PS2 or Redundant power supply
- Two Front Accessible USB port
- Support 14-slot Backplane or ATX MB (9.6'' × 12'')

Specification

- Disk Driver Bay: 5.25'' x3, 3.5'' x1 (External), 3.5'' x1 (Internal).
- Cooling Fan: 1x(120x120x 25mm) cooling fan with air filter
- I/O interface:2xUSB Accessible from the front door
- Support OSD function (front panel)
- Dimension: (WxDxH): 438.1mm × 452.2mm × 177 mm
- Display Type: 8" SVGA TFT LCD
- Resolution: 800 × 600
- Max.color: 262K
- Luminance: 400 cd/m2
- View Angel: 100° (H) , 90° (V)
- Pixel Pitch: 0.2535x 0.2535 mm

- Contrast Ratio: 300 : 1
- Response Time: 80ms
- Power Consumption: 4 W
- LCD MTBF: 10,000hrs

Touch Screen

- Type: Analog resistive type: 25VDC \geq 20M Ω
- Resolution: continuous
- Light transmission: 80% or more
- Controller: RS-232 interface or USB
- Power consumption : < 5V @1mA
- Surface hardness: 3H
- Operating force: \leq 100g
- Life expectancy: 1 Million

Structure Diagram

