

Product Model: SCCS-1111i

1 port RS232 to RS232 Isolation Adapter with 3KV Isolation, with DIN Rail kit



Feature:

- Fully compatible with PC serial COM ports
- 921.6 Kbps maximum baud rate for super fast data transmission
- Transmit and Receive LED supports
- Built-in 15KV ESD protection for all RS-232 port
- 3KV Optical Isolation Protection
- No Drivers needed
- Supports Industrial Specification

Specification	
Hardware	Power Input: 10~30VDC DC JACK Power Consumption: 52mA @24VDC Device Connector: DB9M x 1 Host Connector: DB9F x 1
Serial Interface	Number of ports: 2 port Serial Standard: RS-232
Serial Line Protection	ESD Protection: 15KV ESD Protection for all signals Optical Isolation Protection: 3KV Optical Isolation
Performance	Baud rate: up to 921.6 kbps
Distance	Maximum 15M @ 115.2Kbps
Serial Communication parameters	Data Bits: 5, 6, 7, 8 Stop Bit: 1, 1.5, 2 Parity: None, Even, Odd, Space, Mark
Serial Signals	RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
Physical Characteristics	Housing: PC



Environmental Limits	Operating temperature: -30°C to 75 °C Storage temperature: -40 °C to 85 °C Ambient Relative Humidity: 5 ~ 95% Non-Condensing
Standards and Certifications	CE and FCC supports
Package Content	1 port RS232 to RS232 Isolation Adapter with 3KV Isolation x 1 DIN Rail Kit x 1 Quick Installation Guide x 1