

**Model: SLPM-15T**  
**15" Slim Line - Industrial Panel Monitor with Touch Screen**



### Main Feature

- 15" XGA LED panel support 1024x768 pixels
- 6mm Aluminum Magnesium Alloy front bezel (with PET protection film) - light weight design
- NEMA4 / IP 65 compliant front panel, with Rugged construction design
- Aesthetic ultra-thin front bezel for minimize stain water & dust
- Input signal : VGA + DVI + USB or RS232 (Optional for Touch Screen - 5 wire resistive)
- OSD control keys to optimize the display (Hot-Key for quick "Brightness & Contrast" adjustment)
- Wide Range 12-24VDC Input
- Meet standard VESA hole ( 75x75 & 100X100mm ), support desktop stand/wall mount /swing arm mounting
- Wide Range Operating Temperature -20 °C to 60 °C 

Specification	
Product Model	SLPM-15T
LCD Panel	Display Type : 15" XGA <u>LED Panel</u> Resolution : 1024x768 Max. color : 16.7M Luminance : 400 cd/m2 View Angel : 150° (H) , 140° (V) Pixel Pitch : 0.297 x 0.297 mm Contrast Ratio : 800 : 1 Response Time : 16 ms LED backlight lifecycle : 50,000hrs
Signal Input	VGA + DVI
Protect Glass	3 mm strengthen glass
OSD	Auto; Menu; Left; Right; Exit/Select; Power On/Off (Hot-Key for quick "Brightness & Contrast" adjustment)
Touch Screen	Internal USB or RS-232 <u>industrial grade 5 wire Resistive Touch controller</u>

	Resolution: 4096 x 4096 Light transmission: 80% or more Surface hardness : 3H Operating force : ≤100g Life expectancy : 35 Million Operation system : Window 2000 / XP / Vista / 7 / CE, DOS , Linux
Power Supply	Input: 12-24VDC Wide range
Construction	Aluminum magnesium alloy front panel with heavy-duty steel chassis
Environment	Operating temperature: -20 °C to 60 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak( 11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D ( mm )	Dimensions: 396 x 314 x 49 mm

## Ordering Information

SLPM-15T	15" Slim Line - Industrial Panel Monitor with Touch Screen
(Optional) AC to DC Adapter	12VDC/60watt Power Adapter, input 110-240VAC

## Structure Diagram (Mounting Hole Size: 377 x 301 mm)

Unit: mm

