

Model: SLR-101T-FHD
10.1" Sunlight Readable Full HD Display with PCT Touch

10.1" 1500 NITS HIGH BRIGHTNESS
INDUSTRIAL-GRADE TOUCH MONITOR

1500 Nits 1920x1200 10-Point Touch Auto Dimming HDMI / VGA TPYE-C

50000h
LED PANEL LIFE TIME
A selection of high quality industrial LCD with a longer life time.

OPTIONAL IP65
Features with HDMI / VGA extension cable and IP65 housing.

HDMI / VGA

Main Features

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption...
- 10.1" Full HD LED panel support 1920 x 1200 pixels
- Heavy-duty PVC with Rugged construction design
- Front flat glass (6H Hardness) with projected capacitive Multi Touch Screen
- Supports 10 points multi-touch via USB interface in Windows 7/8.1/10/11
- Input signal: VGA + HDMI + USB (Type C)
- AC 100-240V wide range external AC adapter (with Wide Range 12-24VDC input)
- Meet standard VESA hole (75 x 75mm), support desktop stand / wall mount / swing arm mounting

Application:

- Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial

Specification	
Product Model	SLR-101T-FHD
LCD Panel	Display Type : 10.1'' Full HD <u>LED Panel</u> Resolution : 1920 x 1200 Luminance : 1500 nit View Angel : 170°(H), 170°(V) Contrast Ratio : 1000 : 1 LED backlight lifecycle: 50,000hrs
Signal Input	VGA + HDMI + AV (BNC) + Audio + USB
OSD	Auto; Menu; Left; Right; Exit/Select; Power On/Off
Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 8.1 / 10 / 11; Linux
Power Supply	Input: 12-24VDC Wide-range AC power to DC Adapter: 100-240VAC,50/60Hz to DC12V/3A
Construction	Heavy-duty steel chassis
Environment	Operating temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	250 x 170 x 33 mm
Ordering Information	
SLR-101T-FHD	10.1" Sunlight Readable Full HD Display with PCT Touch
Optional (IP65)	Add IP65 protection with extension cables

Structure Diagram

OUTLINE DIMENSION

