

Model: SSPM-12PCT
12.1" Industrial Stainless Steel Panel Monitor with PCT Touch



Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 12.1" XGA LED panel support 1024x768 pixels
- Front 4mm Stainless Steel bezel with NEMA4 / IP 65 compliance
- Front flat glass (6H Hardness) with projected capacitive Multi Touch Screen
- Supports 10 points multi-touch via USB interface in Windows 7/8.1/10...
- Slim design for Panel mount / Wall mount easy installation
- Input signal : VGA + USB
- Wide Range 12-24VDC input
- Meet standard VESA hole (100X100mm), support desktop stand/wall mount /swing arm mounting

Application:

Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial ...

Specification	
Product Model	SSPM-12-PCT
LCD Panel	Display Type : 12.1" XGA <u>LED Panel</u> Resolution : 1024 x 768 Max. color : 16.7M Luminance : 450 cd/m2 View Angel : 160°(H), 140°(V) Pixel Pitch : 0.297 x 0.297 mm Contrast Ratio : 700 : 1 Response Time : 12 ms LED backlight lifecycle : 50,000hrs
Signal Input	VGA + USB
OSD	Auto; Menu; Left; Right; Exit/Select; Power On/Off

Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 8.1 / 10; Linux
Power Supply	Wide Range 12-24VDC input
Construction	Stainless Steel front panel with heavy-duty steel chassis
Environment	Operating temperature: -0 °C to 60 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	359 x 297 x 48 mm

Ordering Information

SSPM-12PCT	12.1" Industrial Stainless Steel Panel Monitor with PCT Touch
------------	---

Structure Diagram (Mounting Hole Size: 332 x 277 mm)

